

Linea

LX-600

Passive line source speaker for music & speech, 6 × 6,5" / 4 × 1",
1000 W, 136 dB SPL max., approx. 195 × 1500 × 238 mm, install
version



Linea LX-600

The LX-600 is a loudspeaker designed for challenging fixed installations. It combines and optimizes the principles of line array technology in a compact, high performance system: first-class directivity, even dispersion, and a long reach. The slim appearance enables perfect visual integration into the room architecture. The loudspeaker system can be optimally combined with passive and active subwoofers of the X and Perform series and delivers best results with Fohhn DSP power amplifiers.

Main features

- 6 × 6.5" long excursion driver, 4 × 1" compression driver with Waveguide
- Nominal power rating: 1000 W
- Dispersion: 100° × 20° (H × V)
- SPL max.: 136 dB
- High feedback resistance
- Connections: 8-pole Phoenix connector
- High-quality wooden enclosure (multiplex birch) with PU coating
- Available in RAL Classic, NCS or Pantone colors on request
- Versatile mounting and flying accessories
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.

Available with the following color options



Black

Equipped with the following Fohhn technologies



Fohhn Source
Division
Waveguide



Special colors
optional

Technical data

Electroacoustic features	
acoustic design	passive hybrid line source speaker system, 2-way
power rating (nominal)	1000 watts
power rating (program)	2000 watts
power rating (peak)	4000 watts
components	6 × 6.5" long excursion chassis, attached compression chamber with phase board, 4 × 1" compression drivers on Fohhn-Waveguide with self-resetting IPC-HF protection, fully neodymium
sensitivity	101 dB
maximum SPL	136 dB
frequency range	75 Hz – 20 kHz
2-way design	yes
nominal impedance	8 ohms
nominal dispersion (h × v)	100° × 20°
Physical features	
enclosure	multiplex birch plywood, Aluminium
connectors	8-pin Phoenix terminal
dimensions (w × h × d)	approx. 195 × 1500 × 238 mm
weight	29 kg
standard colours	black or white
weather protection	polyurethane coating and water-repellant speaker cone impregnation
front design	acoustic foam, same colour as enclosure
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	8 × M6 and 2 × M8 thread
Optional features	
optional colours	RAL Classic / NCS / Pantone on request
CAAD simulation data	
simulation data	EASE, Fohhn Designer

power rating (nominal/program): according to IEC-60268-5 (long term/short term)
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset
sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset
weight: net weight without optional equipment
Intelligent Protection Circuit (IPC): voltage-controlled semiconductor circuit protecting the HF-driver against overload highly effective and with very short attack time
cut-off frequency: -10 dB under anechoic halfspace-conditions with speaker preset
heat dissipation: pink noise, 6 dB crest, 1/4 Pmax

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

