

Airea

AS-06 ASX

Aktiv subwoofer med Fohhn Aira, 6,5", 109 dB SPL max., 300 × 210 × 380 mm



Airea AS-06 ASX

The AS-06 ASX er den mindste aktive subwoofer i Fohhn Airia system. Den er forbundet via et netværkskabel til den Airia matrix AM-4.4, som leverer netspænding samt digitale lyd- og styresignaler. Den supplerer perfekt seriens nærfelthøjttalere i netværket i den lave ende.



Main features

- 6,5" long excursion driver
- Airia net load: 100 W
- Omfattende DSP- og routing-muligheder via Fohhn Audio Soft
- Tilslutninger: 2 x RJ-45 (Fohhn Airia)
- Kræver kun et enkelt CAT-kabel
- Q-SYS Plugin fås i kombination med Fohhn NA-4 eller ABX-6
- Trækabinet af høj kvalitet (multiplex birkekrydsfiner)
- Kan fås med vejrbestandig PU-belægning som ekstraudstyr
- Kan fås i RAL Classic, NCS eller Pantone-farver på forespørgsel
- Forskellige monteringsmuligheder til faste og midlertidige installationer



Fås med følgende farvevarianter



Sort



Hvid

Udstyret med følgende Fohhn-teknologier



Fohhn Airia



Særlige farver
valgfrit

Mulige indgangsinterfaces for dette produkt

AIREA

Tekniske data

Electroacoustic features	
acoustic design	ultra-compact subwoofer, bass reflex
components	1 × 6.5" long excursion
maximum SPL	109 dB
cut-off frequency	40 Hz
upper crossover frequency	90 / 110 / 130 Hz

Physical features	
enclosure	multiplex birch plywood
connectors	2 × RJ-45
dimensions (w × h × d)	300 × 210 × 380 mm
weight	8 kg
standard colours	textured paint, black
front design	acoustic foam in enclosure colour
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	6 × M6 thread

Optional features	
optional colours	RAL Classic / NCS / Pantone on request

Electronic features	
amplifier type	Pure Path Digital PWM
DSP	Fohhn Audio DSP
audio inputs	2 independent audio channels, AES/EBU 32 kHz – 96 kHz, 16/24 Bit
audio outputs	2 × 300 W intern
amplifier power	2 × 300 W
frequency response	20 Hz – 20 kHz
gain	30 dB
input sensitivity	–6 dB Fullscale
signal/noise ratio	>105 dB/A
THD	
protective circuit	soft start, overtemperature, short circuit, overload
power supply	Airea Net 50 V
power consumption	Standby 5 W, Airea Net Load 100 W
power factor (PFC)	> 90 %
protection	integrated semiconductor fuse
low power	Green Power Standby Mode
emergency current	with extern USV
heat dissipation	100 W, 340 BTU/h, 86 kcal/h
temperature range	0 – 40°C
cooling	passive
weight (electronics)	0.3 kg

Controller	
digital signal processors	2
independent limiters	4
FIR filter	yes
gain	-80 dB – +12 dB
volume	-80 dB – +12 dB
EQ	10-band parametric EQ, gain, +/-12 dB, frequency 10 – 20 kHz, Q 0.1 – 100
selective 3-band limiting	bass / mid / high
limiter / compressor	yes
noise gate	yes
delay	0 – 145 ms (0 – 50 m)
X-over	Linkwitz-Riley 4. order, 24 dB/octave, high pass 10 Hz – 20 kHz, low pass 10 Hz – 20 kHz
user presets	100
system latency	0,95 ms
band-specific time constants	yes
filter technology	56-bit double precision
input	AES/EBU 32kHz – 96 kHz, 16/24 Bit

Remote control and remote monitoring	
remote control	Airea-Net, Fohhn Audio Soft
remote monitoring	temperature, protect, signals, power supply, Fohhn-Net, Fohhn Audio Soft, AES/EBU available
simulation beam	Bassarray

Display LEDs	
sign, identification front LED	blue, blue flashing
network control	receive/send remote control LED
power on / off (standby)	green = on, red = standby, red / green flashing = fault
sign, identification	blue, blue flashing

nominel effekt (peak); maksimal SPL: peak, 20 ms med båndpasfiltreret lyserødt støjsignal i henhold til IEC 60268-2 ved en oktav over frekvensområdets nedre grænse, med højttalerforindstilling
 vægt: nettovægt uden ekstraudstyr
 grænsefrekvens: -10 dB under ekkofrie halvrumsforhold med højttalerforindstilling
 varmeafgivelse: lyserød støj, 6 dB crest, 1/4 Pmax

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Tyskland

Telefon +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

