

Voice Alarm

LEN-20

Passiv 100 V højttaler, EN 54-24 certificeret, 2 × 4", 130° × 60°,
ca. 133 × 230 × 128 mm, vejrbestandig



Voice Alarm LEN-20

LEN-20 er en passiv 100 volt-højttaler, der er certificeret i henhold til EN 54-24 Type B til brug i talalarmsystemer. Som alle produkter i Voice Alarm-serien er den udstyret med et vejrbestandigt, stålforstærket aluminiumshus, hvilket gør den lige velegnet til indendørs og udendørs brug. LEN-højttalerne garanterer fremragende taleforståelighed og lang rækkevidde, selv i vanskelige akustiske omgivelser.



Main features

- 2 × belagt 4" chassis
- Jævn dækning og spredning
- Undertrykkelse af uønskede sideløber takket være Fohhn Source Division Waveguide
- Vejrbestandig uden yderligere beskyttelse (beskyttelsesgrad IP54 i henhold til IEC 529 / EN 60529)
- Nyhed: Fleksibel montering takket være T-slottet på bagsiden
- Fås i forskellige farver (RAL Classic, Pantone, NCS) eller med Fohhn Texture Design
- For at sikre ydeevne og driftssikkerhed kræves Fohhn systemforstærkere inklusive den korrekte højttalerindstilling.



Fås med følgende farvevarianter



Sort



Hvid

Udstyret med følgende Fohhn teknologier



Fohhn Texture Design



Fohhn Source Division Waveguide



100 V valgfri



Særlige farver valgfrit



Mulighed for vejrbestandighed

For detaljerede oplysninger om alle Fohhn teknologier, farvemuligheder og tilslutninger, besøg venligst

www.fohhn.com/en/technologies

Tekniske data

Electroacoustic features

acoustic design	weatherproof passive line source speaker system, closed, suppression of side lobes by Source Division Waveguides
components	2 × 4" drivers with treated cones
sensitivity 1 W @ 4 m in accordance with EN 54-24	79 dB SPL
SPLmax 100 V @ 4 m in accordance with EN 54-24 (trafo S/M/L)	92 dB SPL
2-way design	no
transformer options, power handling in acc. with EN 54-24 100 V (trafo S/M/L)	50 W / - / -
transformer options, power handling in acc. with EN 54-24 70 V (trafo S/M/L)	24.5 W / - / -
impedance 100 % tap (trafo S/L/M)	200 ohm / - / -
impedance 50 % tap (trafo S/M/L)	400 ohm / - / -
impedance 25 % tap (trafo S/M/L)	800 ohm / - / -
nominal directivity (h × v) (–6 dB, average @ 1–4 kHz)	130° × 60°
directivity (h × v) (octave band) in acc. with EN-54-24 @ 500 Hz	360° × 360°
directivity (h × v) (octave band) in acc. with EN 54-24 @ 1000 Hz	190° × 120°
directivity (h × v) (octave band) in acc. with EN 54-24 @ 2000 Hz	120° × 60°
directivity (h × v) (octave band) in acc. with EN 54-24 @ 4000 Hz	95° × 30°

Physical features	
enclosure	weatherproof aluminium housing, powder coated, steel bracings
connectors	terminal connectors capable of receiving up to 4 mm ² , two per pin, terminal cover with dual cable gland for up to 10 mm cable diameter
dimensions (w × h × d)	approx. 133 × 230 × 128 mm
weight (trafo S/M/L)	approx. 3 kg / - / -
standard colours	black (RAL 9005) or white (RAL 9016), powder-coated
certificates	EN 54-24 type B
EN 54-24	1
front design	ball impact resistant grille, galvanized and powder coated in housing colour backed by acoustically transparent foam
mounting points	continuous T-slot at rear

Optional features	
optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design
optional connectors	ceramic terminals capable of receiving up to 2.5 mm ²
optional weather protection	as standard (protection class IP54, in accordance with IEC 529 / EN 90529)

CAAD simulation data	
simulation data	EASE, CLF, Ulysses, Fohhn Designer

vægt: nettovægt uden ekstraudstyr

følsomhed 1 W / SPLmax 100 V @ 4 m i overensstemmelse med EN 54-24: målt i højttalerens fjernfelt, tæl tilbage til 4 m afstand

impedans 100 / 50 / 25 % tap: målt ved en spænding, der producerer 1 W pr. højttalersystem

Fohhn Audio AG
Großer Forst 15
72622 Nürtingen
Tyskland

Telefon +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

