

# Arc

## AS-06

Passive subwoofer for fixed installations, 6.5", 150 W, 112 dB SPL max., 40 Hz – 500 Hz, approx. 300 × 210 × 380 mm



# Arc AS-06

The AS-06 is the smallest passive subwoofer of the Arc series. It has been specially developed for fixed installations and optimally supports the compact fullrange speakers of the Arc, Linea and Integrato series in the low end.



## Main features

- 1 × 6.5" long excursion driver
- 150 W nominal power rating
- Vented enclosure with non-turbulent port design (Fohhn NTP)
- SPL max.: 112 dB
- Connections: 2 × 4-pin terminal
- High-quality wooden enclosure (multiplex birch)
- Available in RAL Classic, NCS or Pantone colors on request
- Optionally available with weatherproof PU coating
- Various mounting options
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.

## Available with the following color options



Black



White



## Equipped with the following Fohhn technologies



Special colors  
optional



Ball impact  
resistant

# Technical data

## Electroacoustic features

acoustic design	vented design, NTP (Non-Turbulent Portdesign)
power rating (nominal)	150 watts
components	1 × 6.5" long excursion
maximum SPL	112 dB
frequency range	40 Hz – 500 Hz
nominal impedance	4 ohms

## Physical features

enclosure	multiplex birch plywood
front design	acoustically transparent foam in enclosure colour
weight	8 kg
protection grille	steel grille, ball impact resistant, powder-coated
standard colours	textured paint, black
mounting points	6 × M6 thread
connectors	2 × 4-pin terminal
dimensions (W × H × D)	approx. 300 × 210 × 380 mm

## Optional features

optional weather protection	polyurethane coating, water-repellent speaker cone impregnation
optional colours	RAL Classic / NCS / Pantone on request

## CAAD simulation data

simulation data	Fohhn Designer
-----------------	----------------

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

