

# Airea

## AS-10 ASX

Active subwoofer with Fohhn Aireas, 2 × 6.5", 115 dB  
SPL max., 430 × 250 × 380 mm



# Airea AS-10 ASX

The AS-10 ASX is a compact, active subwoofer from the Fohhn Airia system. It is connected via a network cable to a master module, through which it also receives the mains voltage and digital audio and control signals. It perfectly complements the nearfield speakers and line source speakers of the series in the low end.



## Main features

- 2 × 6.5" long excursion driver
- Airia Net Load: 200 W
- Extensive DSP and routing options via Fohhn Audio Soft
- Connections: 2 × RJ-45 (Fohhn Airia)
- Requires only a single CAT cable
- High-quality wood enclosure (multiplex birch plywood)
- Optionally available with weatherproof PU coating
- Available in RAL Classic, NCS or Pantone colours on request
- Various mounting options for fixed and temporary installations

## Available with the following color options



Black



White



## Equipped with the following Fohhn technologies



Fohhn Airia



Special colors  
optional

## Possible input interfaces for this product

**AIREA**

# Technical data

## Electroacoustic features

acoustic design	ultra-compact subwoofer, bass reflex
components	2 × 6.5" long excursion
maximum SPL	115 dB
cut-off frequency	42 Hz
upper crossover frequency	90 / 110 / 130 Hz

## Physical features

enclosure	multiplex birch plywood
front design	acoustic foam in enclosure colour
weight	14 kg
protection grille	steel grille, ball impact resistant, powder-coated
standard colours	textured paint, black
mounting points	6 × M6 thread
connectors	1 × RJ-45 in, 1 × RJ-45 link out
dimensions (W × H × D)	430 × 250 × 380 mm

## Optional features

optional colours	RAL Classic / NCS / Pantone on request
------------------	--

**Electronic features**

amplifier type	Pure Path Digital PWM
DSP	Fohhn Audio DSP
audio inputs	2 independent audio channels, AES/EBU 32 kHz – 96 kHz, 16/24 Bit
audio outputs	2 × 300 W intern
amplifier power	2 × 300 W
frequency response	20 Hz – 20 kHz
gain	30 dB
input sensitivity	-6 dB Fullscale
signal/noise ratio	>105 dB/A
THD	<0,05 % typ., <0,01 % 1 kHz -6 dB
protective circuit	soft start, overtemperature, short circuit, overload
power supply	Airea Net 50 V
power consumption	Standby 5 W, Airea Net Load 200 W
power factor (PFC)	> 90 %
protection	integrated semiconductor fuse
low power	Green Power Standby Mode
emergency current	with extern USV
heat dissipation	200 W, 680 BTU/h, 172 kcal/h
temperature range	0 – 40°C
cooling	passive
weight (electronics)	0.3 kg

**Controller**

digital signal processors	2
independent limiters	4
FIR filter	yes
gain	-80 dB – +12 dB
volume	-80 dB – +12 dB
EQ	10-band parametric EQ, gain, +/-12 dB, frequency 10 – 20 kHz, Q 0.1 – 100
selective 3-band limiting	bass / mid / high
limiter / compressor	yes
noise gate	yes
delay	0 – 145 ms (0 – 50 m)
X-over	Linkwitz-Riley 4. order, 24 dB/octave, high pass 10 Hz – 20 kHz, low pass 10 Hz – 20 kHz
user presets	100
system latency	0,95 ms
band-specific time constants	yes
filter technology	56-bit double precision
input	AES/EBU 32 kHz – 96 kHz, 16/24 Bit

## Remote control and remote monitoring

---

remote control	Airea-Net, Fohhn Audio Soft
remote monitoring	temperature, protect, signals, power supply, Fohhn-Net, Fohhn Audio Soft, AES/EBU available
simulation beam	Bassarray

---

## Display LEDs

---

sign, identification front LED	blue, blue flashing
network control	receive/send remote control LED
power on / off (standby)	green = on, red = standby, red / green flashing = fault
sign, identification	blue, blue flashing

---

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

weight: net weight without optional equipment

cut-off frequency: -10 dB under anechoic halfspace-conditions with speaker preset

heat dissipation: pink noise, 6 dB crest, 1/4 Pmax

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

