

X Series

XS-4 active

Active DSP subwoofer for mobile applications, 18",
1500 W amp, 132 dB SPL max., 35 Hz – 130 Hz,
approx. 590 × 600 × 680 mm



X Series XS-4 active

The XS-4 active is a single 18" subwoofer with built-in class-D amplifier and Fohhn DSP. It provides optimal support to the speakers in the X, Linea, Arc and Focus series in the bass range. The powerful Sub is characterized by precise low-frequency reproduction, a high power rating and versatility.



Main features

- 18" long excursion driver
- Digital 1500 W class-D amplifier
- SPL max.: 132 dB
- 2 balanced signal inputs (XLR/jack plus link-out)
- 2 × Speakon outputs for passive tops
- Built-in DSPs with speaker presets, EQ, delay, compressor/limiter, etc.
- Control via intuitive control panel with display or Fohhn Audio Soft
- High-quality wood enclosure (multiplex birch plywood)
- Transport cover with 4 swivel castors included
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Lightweight, only around 39 kg

Available with the following color options



Black



Equipped with the following Fohhn technologies



Fohhn DSP
inside



Special colors
optional

Technical data

Electroacoustic features

acoustic design	ATD acoustic design
components	1 × 18" long excursion, neodymium
maximum SPL	132 dB
amplifier output	1500 W
frequency range	35 Hz – 130 Hz

Physical features

enclosure	multiplex birch plywood
front design	acoustic foam
thread plate for distance piece	M20
protection grille	steel grille, ball impact resistant, powder-coated
weight	approx. 39 kg
standard colours	textured paint, black
handles	2 side handle
transport wheels	wheel board
dimensions (W × H × D)	approx. 590 × 600 × 680 mm

Optional features

optional weather protection	polyurethane coating, water-repellent speaker cone impregnation
optional colours	RAL Classic / NCS / Pantone on request

Electronic features

power supply	195 V – 250 V AC 50/60 Hz, max. 6A
temperature range	0 – 45°C
cooling	convection cooling, force cooling, if necessary temperature-controlled fan
weight (electronics)	approx. 1.8 kg power supply and amplifier

Controller

digital signal processors	2
independent limiters	8
selective 3-band limiting	bass / mid / high
band-specific time constants	yes
filter technology	56-bit double precision
AD	AD/DA 24 bit / 48 kHz
controls	Select potentiometer, 4 buttons for DSP handling, ground/lift switch, Power on/off switch
indicator LEDs	4 line display, 2 × Signal/Clip LED, 2 × protect LED, receive/send remote LED

Remote control and remote monitoring

remote control	Fohhn Audio Soft, Fohhn Net
remote monitoring	temperature, protect, signals

Connections

outputs (for recording or stacking)	2 × NL4 Neutrik Speakon for Top Speaker (stereo), from 130 Hz 2 × 4 ohms (stereo) or 1 × 8 ohms (bridge mode)
signal	Input jack, 2 × XLR link jacks
inputs	2 × XLR/jacks, multifunctional input jacks
mains	2 × Powercon mains jacks in and thru

integrated digital power amplifier

EIA amplifier power	2 × 750 W (1 kHz, THD+N < 1%)
bridge mode	1500 W
amplification	32 dB
input sensitivity	1.4 V
input impedance	10 kOhm
frequency response	20 Hz – 20 kHz
S/N ratio	>105 dBA
protective circuit	switch-on delay, soft start, impedance- and short-circuit protection, DC protect, temperature monitoring

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

