

# Linea

## LS-2

Passive subwoofer with line source enclosure, 2 × 4", 2 × passive radiator, 100 W, 106 dB SPL max., 133 x 655 x 128 mm



# Linea LS-2



LS-2 is a subwoofer with a slim design enclosure. The Fohhn Sub Extension system and powerful 4" long excursion drivers guarantee a rich, convincing bass reproduction. With all Fohhn line source speakers, which also have a T-slot enclosure, it can be integrated visually perfect in a line.

## Main features

- 2 × 4" long excursion driver and 2 passive radiators
- Nominal power rating: 100 W
- Max. SPL: 106 dB
- Flexible mounting thanks to continuous T-slot at the rear
- Dimensions: 133 × 655 × 128 mm
- Weatherproof according to IP54 with Cable Gland Set
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.

Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Fohhn Texture  
Design



Special colors  
optional



Weatherproof  
execution

# Technical data

## Electroacoustic features

acoustic design	Subwoofer, passive
power rating (nominal)	100 W
components	2 × 4" long excursion woofer / 2 × passive radiator
maximum SPL	106 dB
cut-off frequency	45 Hz
nominal impedance	4 ohms

## Physical features

enclosure	aluminum
protection class acc. to IEC529/EN60529	IP44
front design	steel grille in enclosure colour
protection grille	steel grille, powder-coated
weight	4.7 kg
standard colours	black or white powder coated
mounting points	continuous T-slot at the rear
connectors	2 × 2-pin Phoenix terminal
dimensions (W × H × D)	133 × 655 × 128 mm

## Optional features

optional weather protection	IP54 with Cable Gland Set
optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

