

Linea

LC-220 1. generation

Passive line source speaker, optimised for speech, 18 × 4", 440 Watt, 133 dB SPL max., approx. 130 × 2200 × 120 mm



Linea LC-220 1. generation

The LC-220 is a passive line source speaker for fixed installations. It is optimized for excellent speech reproduction and is ideally suited to both indoor and outdoor applications thanks to its weatherproof aluminum enclosure. The renowned Fohhn line source speakers combine the advantages of line arrays – such as directionality, homogeneous dispersion and reach – in a compact system. The slim aluminum housing enables perfect visual integration into the room architecture.

Main features

- 18 × 4" driver
- Nominal power rating: 440 W
- Frequency range: 120 Hz – 12 kHz
- Suppression of unwanted side lobes thanks to Fohhn Source Division Waveguide
- Perfect speech intelligibility and long reach
- Low impedance technology
- Weatherproof without additional protection (degree of protection IP54 according to IEC 529 / EN 60529)
- Available in different colors (RAL Classic, Pantone, NCS) or with Fohhn Texture Design
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.

Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Fohhn Texture Design



Fohhn Source Division Waveguide



Special colors optional



Weather-resistance possible

For detailed information about all Fohhn technologies, color options and connections, please visit www.fohhn.com/en/technologies

Technical data

Electroacoustic features

acoustic design	weatherproof passive loudspeaker, closed, passive 2-way CD crossover, suppression of side lobes by Source Division Waveguides
power rating (nominal)	440 watts
power rating (program)	880 watts
power rating (peak)	1760 watts
components	18 × 4" treated drivers
sensitivity	101 dB SPL
maximum SPL	133 dB SPL
frequency range	120 Hz – 12 kHz
2-way design	yes
nominal impedance	4 ohm
nominal dispersion (h × v)	130° × 14°

Physical features

enclosure	weatherproof aluminium housing, powder coated, steel bracings
connectors	screwed terminal connectors capable of receiving up to 4 mm ² , two per pin, terminal cover with dual cable gland for up to 10 mm cable diameter
dimensions (w × h × d)	approx. 130 × 2200 × 120 mm
weight	16 kg
standard colours	black (RAL 9005) or white (RAL 9016), powder coated
weather protection	as standard (protection class IP54, in accordance with IEC 529 / EN 90529)
front design	ball impact resistant grille, galvanized and powder coated in enclosure colour, backed by acoustically transparent foam
mounting points	10 × M6 screw threads

Optional features

optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design
optional connectors	ceramic terminals capable of receiving up to 2.5 mm ²
optional weather protection	protection class IP54, weatherproof without additional protective measures

CAAD simulation data

simulation data	EASE, CLF, Ulysses, Fohhn Designer
-----------------	------------------------------------

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

nominal dispersion: -6 dB compared to the main dispersion axis, averaged 1 – 4 kHz

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

