

X Series

XS-30 passive

Passive subwoofer for mobile applications, 15", 700 W, 128 dB
SPL max., 35 Hz – 500 Hz, approx. 430 × 590 × 520 mm



X Series XS-30 passive

The XS-30 passive is a powerful 15" subwoofer. It is characterized by precise low-frequency reproduction, a high power rating and versatility.



Main features

- 15" long excursion driver
- Power rating: 700 W
- SPL max.: 128 dB
- Connections: 4 × Speakon
- High-quality wood enclosure (multiplex birch plywood)
- 2 built-in transport castors
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Lightweight, only about 28 kg
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Special colors
optional

Technical data

Electroacoustic features	
acoustic design	vented design
power rating (nominal)	700 watts
components	1 × 15" long excursion, neodymium
sensitivity	98 dB
maximum SPL	128 dB
frequency range	35 Hz – 500 Hz
nominal impedance	8 ohms

Physical features	
enclosure	multiplex birch plywood
connectors	4 × NL4 Neutrik Speakon
dimensions (w × h × d)	approx. 430 × 590 × 520 mm
thread plate for distance piece	M20
weight	approx. 28 kg
standard colours	textured paint, black
handles	2 side handle, 2 edge handle
transport wheels	2 wheels
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder-coated

Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

CAAD simulation data	
simulation data	Fohhn Designer

power rating (nominal/program): according to IEC-60268-5 (long term/short term)
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset
sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset
weight: net weight without optional equipment

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

