

# Media

# Scale-Bar Cam

Videobar, passive, 2 × 4" woofer / 2 × 0.75" tweeter/ 2 × Fohhn Sub Extension









### Media Scale-Bar Cam

Scale–Bar is a videobar that boasts pro audio quality and is optimally suited for use in conference and meeting rooms. All components and settings have been developed to achieve the highest quality media sound and speech intelligibility. Even when video conferencing, the person on the other end always sounds pleasant and natural – almost as if the person was in the room. This makes every meeting a success and ensures that you are well understood. The integrated Fohhn Sub Extensions also ensure powerful bass reproduction for music and film, without requiring an additional subwoofer. If required, we can customize the enclosure length, so it fits your screen perfectly. The enclosure is prepared for the installation of a conference camera (recommended: Huddly IQ).

To operate the videobar you will need the MA-4.100 system amplifier, which ensures optimal sound with the corresponding speaker presets as well as safe operation. And thanks to the integrated Fohhn DSP technology, the sound can be perfectly adapted to the room if necessary.

#### Main features

- 2 × 4" woofer / 2 × 0.75" tweeter/ 2 × Fohhn Sub Extension
- Power rating nominal: 2 × 50 W
- SPL max.: 107 dB
- Frequency range: 44 Hz 20 kHz
- Clear sound with full bass and optimal speech intelligibility
- Special colours available (RAL Classic, NCS, Pantone, Fohhn Texture Design)
- Flexible mounting thanks to continuous T-slot at rear
- Mounting accessories available
- 2 slot nuts included in scope of delivery
- Different camera models applicable (recommended: Huddly IQ)
- Camera cover in the form of a black magnetic film (7 cm diameter) included
- Attention: The loudspeaker can be operated with Fohhn system amplifiers and the correct speaker preset only.

Available with the following color options



Black

Equipped with the following Fohhn technologies



Fohhn Texture



Special colors



Scalable enclosure

## **Technical data**

### **Electroacoustic features**

power rating (nominal)	2 × 50 W
power rating (program)	2 × 100 W
power rating (peak)	2 × 200 W
components	2 × 4" woofer / 2 × 0.75" tweeter/ 2 × Fohhn Sub Extension
maximum SPL	107 dB
frequency range	44 Hz - 20 kHz
nominal impedance	2 × 4 ohms

### Physical features

enclosure	aluminum
connectors	Phoenix connector
dimensions (w × h × d)	1220 mm (up to 2202 mm) × 133 mm × 128 mm
standard colours	black or white, powder-coated
front design	metal grille in enclosure colour
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	continuous T-slot at rear

### **Optional features**

optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design
•	ı ,

### **CAAD** simulation data

		-
ılation data	Fohhn Designer	

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

Fohhn Audio AG Großer Forst 15 72622 Nuertingen Germany Phone +49 7022 93323-0 Fax +49 7022 93324-0 www.fohhn.com info@fohhn.com

