

# X Series

## XS-30 passive

Passive subwoofer for mobile applications, 15", 700 W, 128 dB  
SPL max., 35 Hz – 500 Hz, approx. 430 × 590 × 520 mm



# X Series XS-30 passive

The XS-30 passive is a powerful 15" subwoofer. It is characterized by precise low-frequency reproduction, a high power rating and versatility.



## Main features

- 15" long excursion driver
- Power rating: 700 W
- SPL max.: 128 dB
- Connections: 4 × Speakon
- High-quality wood enclosure (multiplex birch plywood)
- 2 built-in transport castors
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Lightweight, only about 28 kg
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



## Available with the following color options



Black



White

## Equipped with the following Fohhn technologies



Special colors  
optional

# Technical data

Electroacoustic features	
acoustic design	vented design
power rating (nominal)	700 watts
components	1 × 15" long excursion, neodymium
sensitivity	98 dB
maximum SPL	128 dB
frequency range	35 Hz – 500 Hz
nominal impedance	8 ohms

Physical features	
enclosure	multiplex birch plywood
connectors	4 × NL4 Neutrik Speakon
dimensions (w × h × d)	approx. 430 × 590 × 520 mm
thread plate for distance piece	M20
weight	approx. 28 kg
standard colours	textured paint, black
handles	2 side handle, 2 edge handle
transport wheels	2 wheels
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder-coated

Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

CAAD simulation data	
simulation data	Fohhn Designer

power rating (nominal/program): according to IEC-60268-5 (long term/short term)  
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset  
sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions  
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset  
weight: net weight without optional equipment

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

