

X Series

XS-4 passive

Passive subwoofer for mobile applications, 18", 800 W, 132 dB
SPL max., 35 Hz – 500 Hz, approx. 590 × 600 × 680 mm



X Series XS-4 passive

The XS-4 passive is a powerful single 18" subwoofer. It is characterized by precise low-frequency reproduction, a high power rating and versatility.



Main features

- 18" long excursion driver
- Power rating: 800 W
- SPL max.: 132 dB
- Connections: 4 × Speakon
- High-quality wood enclosure (multiplex birch plywood)
- Transport cover with 4 swivel castors included
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Lightweight, only about 38 kg
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



Available with the following color options



Black

Equipped with the following Fohhn technologies



**Special colors
optional**

Technical data

Electroacoustic features	
acoustic design	ATD acoustic design
power rating (nominal)	800 watts
components	1 × 18" long excursion, neodymium
sensitivity	99 dB
maximum SPL	132 dB
frequency range	35 Hz – 500 Hz
nominal impedance	8 ohms

Physical features	
enclosure	multiplex birch plywood
connectors	4 × NL4 Neutrik Speakon
dimensions (w × h × d)	approx. 590 × 600 × 680 mm
thread plate for distance piece	M20
weight	approx. 38 kg
standard colours	textured paint, black
handles	2 side handles, M20 thread for pole mount
transport wheels	detachable 4-wheel board
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder-coated

Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

CAAD simulation data	
simulation data	Fohhn Designer

power rating (nominal/program): according to IEC-60268-5 (long term/short term)
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset
sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset
weight: net weight without optional equipment

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

