

Linea Focus

DLI-130 (mobile)

Système de line source active avec orientation du faisceau
pour applications mobiles, 8 × 4", 124 dB SPL max., 133 × 1358 ×
128 mm



Analog

AES/EBU

AIREA®

Dante™

Linea Focus DLI-130 (mobile)



La DLI-130 est une enceinte de line source compacte et contrôlable électroniquement, issue de la série primée Focus. Ces haut-parleurs de qualité et performants sont le premier choix pour les applications vocales et musicales professionnelles. Grâce à la technologie Fohhn Beam Steering, elles peuvent être intégrées de manière presque invisible et offrent les meilleurs résultats dans les environnements acoustiques complexes.

Main features

- 8 × 4" haut-parleurs haute performance (réponse en fréquence : 60 Hz - 17 kHz)
- Amplificateur numérique 8 canaux intégré, 8 canaux DSP
- SPL max : 124 dB
- Interface d'entrée en option Analogue, AES/EBU + Fohhn Aireia, Dante Ultimo avec Fohhn Net Control (DUC) ou Dante Brooklyn avec Fibre (DBF)
- Contrôle pratique en temps réel de la dispersion verticale avec Fohhn Audio Soft
- Largeur du faisceau vertical : 0° à 90°, angle d'inclinaison sonore : -40° à +40° (ajusté par incréments de 0,1°)
- Centre acoustique déplaçable sur toute la longueur de la colonne
- Technologie Fohhn Two Beam (deux faisceaux de dispersion indépendants)
- Fohhn Side Lobe Free Technology (suppression des lobes latéraux)
- Disponible en RAL, NCS, Pantone et avec Fohhn Texture Design
- Intégration dans les systèmes d'évacuation conformément à la norme DIN EN 60849 / VDE 0828
- Intégration dans les systèmes de contrôle des médias tels que Crestron, AMX, Extron et autres
- Plugin Q-SYS disponible
- Nouveau : assemblage flexible grâce à la gorge en 'T' située à l'arrière



Disponible avec les options de couleur suivantes



Noir



Blanc

Équipé des technologies suivantes de Fohhn



Fohhn Texture
Design



Fohhn Beam
Steering
Technology



Fohhn Source
Division
Waveguide



Fohhn Airea



Fohhn DSP à
l'intérieur de



Couleurs
spéciales en
option



Auto Power
Save

Interfaces d'entrée possibles pour ce produit

Analog

AES/EBU

AIREA®

@Dante™

Pour des informations détaillées sur toutes les technologies, options de couleur et connexions de Fohhn, veuillez consulter le www.fohhn.com/en/technologies.

Données techniques

Electroacoustic features	
acoustic design	electronically steerable line source speaker
components	8 × 4" impregnated (fully neodymium)
maximum SPL (1 m)	124 dB
frequency range	60 Hz – 17 kHz
operational mode	active, 8 × DSP amplifiers, Class-D
nominal dispersion, horizontal	110°
vertical beam width, digitally controlled	0° to +90° in 0.1° increments
vertical inclination angle, digitally controlled	–40° to +40° in 0.1° increments
acoustic centre	both beams moveable between 0 – 100 % (from speaker bottom to top)
Physical features	
enclosure	aluminum
dimensions (w × h × d)	133 × 1358 × 128 mm
weight	approx. 9.4 kg
standard colours	black or white powder coated
front design	front grille in housing colour
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	continuous T-slot at rear
Optional features	
optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design
CAAD simulation data	
simulation data	EASE, Fohhn Designer

Electronic features	
amplifier type	Pure Path Digital PWM
support for AES67	only with Dante versions
DSP channels, Fohhn Audio DSP	8
amplifier power	8 × 100 W
frequency response	20 Hz – 20 kHz
gain	25 dB
input sensitivity	0 dBFS with AES or Dante versions; 1.4 V with Analog
signal/noise ratio	>105 dB/A
tilt sensor	yes
password protection	yes
auto power save	adjustable from 1 s to 12 h, or permanently active
protective circuit	soft start, overtemperature, short circuit, overload
power supply	100 V – 240 V AC 50/60 Hz, power supply with Power Factor Correction (PFC)
power consumption	Standby 5 W, max. 200 W
power factor (PFC)	> 90 %
low power	Green Power Standby Mode
heat dissipation	70 W, 239 BTU/h, 60 kcal/h (Pink Noise, 6 dB crest, 1/4 Pmax)
temperature range	0 – 40 °C
cooling	temperature-controlled fan
weight (electronics)	approx. 2 kg

Controller	
digital signal processors	2
independent limiters	6
FIR filter	yes
gain	-80 dB – +12 dB
volume	-80 dB – +12 dB
EQ input	10 fully parametric filters, Gain +/-12 dB, Frequency 10 Hz – 20 kHz, Q 0.1 – 100
EQ output	10 fully parametric filters, Gain +/-12 dB, Frequency 10 Hz – 20 kHz, Q 0.1 – 100
selective 3-band limiting	bass / mid / high
limiter / compressor	2 × Input, 1 × Output
noise gate	2 × Input, 1 × Output
X-over	Linkwitz-Riley 4th order, 24 dB/octave, high pass 10 Hz – 20 kHz, low pass 10 Hz – 20 kHz, 2 × input, 1 × output in each case
delay input	0.01 – 350 ms or 3.4 mm – 120 m each
delay output	0.01 – 650 ms or 3.4 mm – 220 m each
user presets	100
simulation beam	Fohhn Net, Fohhn Audio Soft
system latency	1.8 ms with AES, 2.4 ms with Analog, Dante +1.8 ms with Dante versions
band-specific time constants	yes
filter technology	80-bit double precision
AD (with Analog input)	24 bit / 96 kHz

Inputs and outputs	
audio inputs	optionally 1 × AES/EBU + 1 × Airea, 2 × Analog (transformer balanced) or Dante
redundancy	only with Dante DBF version (Dante Primary & Secondary)
audio input channels DSP	2
audio link	only with Analog version (2)

Remote control and remote monitoring	
remote control	Fohhn Audio Soft, Fohhn Net
remote monitoring	temperature, protect, signals, power supply, Fohhn Net, Fohhn Audio Soft, tilt sensor, pilot tone
pilot tone monitoring	activatable, detectable in Master (on both inputs)
fault message contact	only with AES or Analog version (1 × relay 2 × alternate, 3-pin Phoenix)
switching contact	only with AES or Analog version (load preset, standby on/off)

Connections

mains connection (internal)	1 × WAGO 2-pin, grounding screwed
signal inputs	AES: Phoenix 3-pin + Phoenix 3-pin Fohhn Net + RJ-45 Airea, Analog: 2 × Phoenix 3-pin + Phoenix 3-pin Fohhn Net, Dante (DUC): RJ-45 100BASE-TX Ethernet (Dante + Fohhn Net), Dante (DBF): 2 × RJ-45 1000BASE-T Ethernet + 2 × SFP port (Dante + Fohhn Net)
signal link	only with AES (1 × Phoenix 3-pin Fohhn Net) or Analog version (2 × Phoenix 3-pol for audio, 1 × Phoenix 3-pin Fohhn Net)
fault message contact	only with AES or Analog version (1 × Phoenix 3-pin, 1 × Phoenix 3-pin link)
switching contact	only with AES or Analog version (1 × Phoenix 3-pin)

Display

power on / off (standby)	only with AES or Analog version (green = on, red = standby, red flashing = fault, blue = sign)
network control	only with AES or Analog version (receive/send remote control LED)

puissance nominale (crête) ; SPL maximum : crête, 20 ms avec un signal de bruit rose filtré en bande passante selon IEC 60268-2 à une octave au-dessus de la limite inférieure de la bande de fréquences, avec enceinte pré-réglé

bande de fréquences : -10 dB dans des conditions de demi-espace anéchoïque avec enceinte pré-réglé

poids : poids net sans équipement optionnel

dissipation thermique : bruit rose, crête de 6 dB, 1/4 Pmax

dispersion nominale : -6 dB par rapport à l'axe de dispersion principal, moyenne 1 - 4 kHz

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

