

X Series

XS-22 active

Active DSP subwoofer for mobile applications, 12", 1.500 W
amp, 127 dB SPL max., 38 Hz – 130 Hz, approx. 520 × 420 × 430
mm



X Series XS-22 active

The XS-22 active is a compact subwoofer with integrated class-D amplifier and Fohhn DSP. It provides optimal support to the compact speakers in the X, Linea, Arc and Focus series in the bass range. The sub is characterized by precise low-frequency reproduction, a high power rating and versatility.



Main features

- 12" long excursion driver
- Digital 1500 W class-D amplifier
- SPL max.: 127 dB
- Non-turbulent port design (NTP)
- 2 balanced signal inputs (XLR/jack plus link-out)
- 2 × Speakon outputs for passive tops and additional sub
- Built-in DSPs with speaker presets, EQ, delay, compressor/limiter, etc.
- Control via intuitive control panel with display or Fohhn Audio Soft
- High-quality wood enclosure (multiplex birch plywood)
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating



Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Fohhn DSP
inside



Special colors
optional

For detailed information about all Fohhn technologies, color options and connections, please visit www.fohhn.com/en/technologies

Technical data

Electroacoustic features	
acoustic design	vented design
components	1 × 12" long excursion
maximum SPL	127 dB
amplifier output	1.500 W
frequency range	38 Hz – 130 Hz
Physical features	
enclosure	multiplex birch plywood
dimensions (w × h × d)	approx. 520 × 420 × 430 mm
thread plate for distance piece	M20
weight	approx. 25 kg
standard colours	textured paint, black
handles	2 edge handle
transport wheels	none
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder-coated
Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation
Electronic features	
power supply	195 V – 250 V AC 50/60 Hz, max. 6A
temperature range	0 – 45°C
cooling	convection cooling, force cooling, if necessary temperature-controlled fan
Controller	
digital signal processors	2
independent limiters	8
selective 3-band limiting	bass / mid / high
band-specific time constants	yes
filter technology	56-bit double precision
AD (with Analog input)	AD/DA 24 bit / 48 kHz
controls	Select potentiometer, 4 buttons for DSP handling, ground/lift switch, Power on/off switch
indicator LEDs	4 line display, 2 × Signal/Clip LED, 2 × protect LED, receive/send remote LED

Remote control and remote monitoring

remote control	Fohhn Audio Soft, Fohhn Net
remote monitoring	temperature, protect, signals

Connections

inputs	2 × XLR/jacks, multifunctional input jacks
signal	Input jack, 2 × XLR link jacks
mains	2 × Powercon Netzbuchse in und thru
outputs (for recording or stacking)	2 × NL4 Neutrik Speakon for Top Speaker and Slave Sub, from 130 Hz 2 × 4 ohms (stereo) or 1 × 8 ohms (bridge mode) mains

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

