

Airea

LX-60 ASX

Actieve lijnbronluidspreker voor muziek en spraak met Fohhn
Airea, 4 × 4" / 1", W, 119 dB SPL max., 130 × 640 × 120 mm



Airea LX-60 ASX

De LX-60 ASX is een actieve 2-weg lijnbronluidspreker van het Fohhn Airia systeem. Hij wordt via een netwerkkabel aangesloten op de Airia matrix AM-4.4 die zowel de netspanning als de digitale audio- en besturingssignalen levert. De LX-60 ASX garandeert weergave van spraak en muziek van wereldklasse in een geavanceerd, volledig digitaal audionetwerk: Fohhn Airia.

Main features

- 4 × 4 "lange excursie driver, 1 × 1" compressie driver op waveguide
- Hoge en middentonen kunnen afzonderlijk worden geregeld met een 2-kanaals versterker
- Uitgebreide DSP en routing mogelijkheden via Fohhn Audio Soft
- Airia Netto belasting: 100 W
- Gerichte spreiding: 130 ° × 30 ° (H × V)
- Aansluitingen: 2 × RJ-45 (Fohhn Airia)
- Vereist slechts een enkele CAT-kabel
- Q-SYS Plugin beschikbaar in combinatie met Fohhn NA-4 of ABX-6
- Verkrijgbaar in RAL Classic, NCS of Pantone kleuren op aanvraag
- Diverse montagemogelijkheden voor vaste en tijdelijke installaties



Verkrijgbaar met de volgende kleuropties



Zwart



Wit

Uitgerust met de volgende Fohhn technologieën



Fohhn Texture
Design



Fohhn Aireal



Speciale
kleuren
optioneel

Mogelijke invoerinterfaces voor dit product

AIREA®

Technische gegevens

Electroacoustic features	
acoustic design	active hybrid line source speaker system, 2-way
components	4 × 4" long excursion with treated cones, 1 × 1" compression driver on Fohhn-Waveguide, fully neodymium
maximum SPL	119 dB
operational mode	active, 2 × Class-D DSP amplifier
frequency range	75 Hz – 20 kHz
2-way design	yes
nominal dispersion (h × v)	130° × 30°

Physical features	
enclosure	aluminum
connectors	2 × RJ-45
dimensions (w × h × d)	130 × 640 × 120 mm
weight	4.4 kg
standard colours	black or white powder coating
front design	metal grille in enclosure colour, backed by acoustically transparent foam
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	8 × M6 thread

Optional features	
optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design

CAAD simulation data	
simulation data	EASE, Fohhn Designer

Electronic features	
amplifier type	Pure Path Digital PWM
DSP	Fohhn Audio DSP
audio inputs	2 independent audio channels, AES/EBU 32 kHz – 96 kHz, 16/24 Bit
audio outputs	2 × 300 W intern
amplifier power	2 × 300 W
frequency response	20 Hz – 20 kHz
gain	30 dB
input sensitivity	–6 dB Fullscale
signal/noise ratio	>105 dB/A
THD	
protective circuit	soft start, overtemperature, short circuit, overload
power supply	Airea Net 50 V
power consumption	Standby 5 W, Airea Net Load 100 W
power factor (PFC)	> 90 %
protection	integrated semiconductor fuse
low power	Green Power Standby Mode
emergency current	with external USV
heat dissipation	100 W, 340 BTU/h, 86 kcal/h
temperature range	0 – 40°C
cooling	passive
weight (electronics)	0.3 kg

Controller	
digital signal processors	2
independent limiters	4
FIR filter	yes
gain	-80 dB – +12 dB
volume	-80 dB – +12 dB
EQ	10-band parametric EQ, gain, +/-12 dB, frequency 10 – 20 kHz, Q 0.1 – 100
selective 3-band limiting	bass / mid / high
limiter / compressor	yes
noise gate	yes
delay	0 – 145 ms (0 – 50 m)
X-over	Linkwitz-Riley 4. Ordnung (24 dB/Oktave), Highpass 10 Hz – 20 kHz, Lowpass 10 Hz – 20 kHz
user presets	100
system latency	0,95 ms
band-specific time constants	yes
filter technology	56-bit double precision
input	AES/ABU 32 kHz – 96 kHz, 16/24 Bit

Remote control and remote monitoring	
remote control	Airea-Net, Fohhn Audio Soft
remote monitoring	temperature, protect, signals, power supply, Fohhn-Net, Fohhn Audio Soft, AES/EBU available

Display LEDs	
sign, identification front LED	blue, blue flashing
network control	receive/send remote control LED
power on / off (standby)	green = on, red = standby, red / green flashing = fault
sign, identification	blue, blue flashing

nominaal vermogen (piek); maximale SPL: piek, 20 ms met bandgefilterd roze ruissignaal overeenkomstig IEC 60268-2 bij één octaaf boven de ondergrens van het frequentiebereik, met luidspreekervoorinstelling
 frequentiebereik: -10 dB onder anechoïsche halfruimte-condities met luidspreekervoorinstelling
 gewicht: nettogewicht zonder optionele apparatuur
 warmteafvoer: roze ruis, 6 dB crest, 1/4 Pmax
 nominale dispersie: -6 dB ten opzichte van de hoofddispersie-as, gemiddeld 1 – 4 kHz

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Duitsland

Telefoon +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

