

# Converters

## A-2 live

USB audiointerface with AES/EBU output (XLR)



# Converters A-2 live

The A-2 live is a USB audio interface with digital AES/EBU output. It enables the high-quality and trouble-free transmission of audio signals from a computer to a professional sound system and can be used without the installation of drivers.



## Main features

- AES/EBU output via XLR
- No hum thanks to galvanic isolation
- No separate power supply required
- 16 bit 44.1 / 48 kHz

Available with the following color options



Black



For detailed information about all Fohhn technologies, color options and connections, please visit [www.fohhn.com/en/technologies](http://www.fohhn.com/en/technologies)

# Technical data

Physical features	
connectors	USB 1.1 Full Speed
dimensions (w × h × d)	105 × 45 × 50 mm
Electronic features	
power supply	USB powered (no separate power supply is required)
audio outputs	AES / EBU, galvanically isolated
resolution	16
sample rate	44,1 / 48 kHz
maximum cable length AES / EBU	100
maximum cable length USB	5

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

