


# Arc

## AT-07

Passive fullrange speaker for fixed installations, 6.5"/1", 150 W,  
123 dB SPL max., approx. 195 x 380 x 230 mm



# Arc AT-07



The AT-07 is a passive fullrange speaker for fixed installations. It impresses with its high performance capacity and compact dimensions.

In addition to outstanding technical features, the models of the Arc series are generally characterized by their attractive design.

## Main features

- 6.5" / 1" compression driver on rotatable CD horn, electronic high frequency protection
- Nominal power rating: 150 watts at 16 ohms
- Dispersion: 90 ° x 60 ° (H x V)
- SPL max.: 123 dB
- Dual connection panel: Speakon and 4-pole connector (inside, with cable outlet)
- High-quality wooden enclosure (multiplex birch)
- Available in RAL Classic, NCS or Pantone colors on request
- Optionally available with weatherproof PU coating
- Various mounting options
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.

Available with the following color options



Black



White

Equipped with the following Fohhn technologies



100 V optional



Special colors optional



Ball impact resistant

# Technical data

## Electroacoustic features

acoustic design	passive loudspeaker, 2-way, vented design
power rating (nominal)	150 watts
power rating (program)	300 watts
power rating (peak)	600 watts
components	6,5" / 1" on rotatable CD-horn, with self-resetting Polyswitch-HF protection
sensitivity	96 dB
maximum SPL	123 dB
frequency range	65 Hz – 20 kHz
2-way design	yes
nominal impedance	16 ohm
nominal dispersion (h × v)	90° x 60°

## Physical features

enclosure	multiplex birch plywood, reinforced with steel braces
connectors	1 x Neutrik NL4 Speakon and 4-pole connector inside
dimensions (w × h × d)	approx. 195 x 380 x 230 mm
weight	approx. 7 kg
standard colours	textured finish black or white
front design	acoustic foam, same colour as enclosure
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	9 x M6 thread

## Optional features

optional colours	RAL Classic / NCS / Pantone on request
integrated 100 V transformer	60 W / 30 W / 15 W
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

## CAAD simulation data

simulation data	EASE, Ulysses, Fohhn Designer
-----------------	-------------------------------

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

nominal dispersion: -6 dB compared to the main dispersion axis

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

