



Perform

PS-850

无源高性能低音炮，2×18英寸，2000瓦，截止频率：27赫兹，
1200×600×900毫米



履约PS-850

PS-850 是Perform系列中一个强大而灵活的双18 "低音炮。这款无源低音炮具有直射式和倒相孔的外壳，是对Focus Venue 模块和PT-70扬声器的完美补充。与带DSP的DI放大器配合使用，它可以为音乐厅、俱乐部、体育场和露天活动提供精确而有力的声音。PS-850 完全适用于水平、垂直或端射低频阵列，但也适用于心形设置。



Main features

- 2 × 18 "长振幅驱动器，4 "音圈
- 防水锥体
- 额定功率：2000W
- 最大声压级: 142 dB
- 低切频率：27赫兹
- 高质量的多层桦木夹板外壳，有防刮的PU涂层
- 前面和后面各有2个Speakon端口，用于心形操作
- 2×钢制加固槽，可选索具机械 (Fohhn Interlock System)
- 用于支撑杆的M20螺纹
- 多功能的附件，如运输盖、前盖和滑车
- 注意：扬声器只能与Fohhn系统功放和正确的扬声器预置一起使用。



有以下颜色可供选择



黑色

配备了以下Fohhn技术



可吊挂的产品



Fohhn Interlock System



可能具有耐候性

技术数据

Electroacoustic features	
acoustic design	direct radiating, vented design, NTP (Non-Turbulent-Port design)
power rating (nominal)	2000 watts
components	2 × 18" long excursion chassis with 4" voice coil, water-resistant cones
maximum SPL	142 dB
cut-off frequency	27 Hz
nominal impedance	4 ohms
Physical features	
enclosure	multiplex birch plywood
connectors	rear: 2 × Neutrik NL4 Speakon, recessed front: 2 × Neutrik NL4 Speakon, for cardioid setups
dimensions (w × h × d)	1200 × 600 × 900 mm
weight	120/110 kg with/without rigging system
finish	polyurethane coating, black
handles	4 handles on each side
transport wheels	2 fittings for optional wheel board
miscellaneous	2 rubber skids on bottom, 2 mating slots on top, 4 rubber feet on each side, 1 fitting for cable strain relief on rear panel
protection grille	hexagonal perforated steel grille, powder-coated in enclosure colour, backed by acoustically transparent foam
mounting points	1 × M20 thread for distance rod, 4 × slot for rigging system, 2 × catches for front panels
Optional features	
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation
CAAD simulation data	
simulation data	Fohhn Designer

额定功率（标称/程序）：根据IEC-60268-5（长期/短期）
额定功率（峰值）；最大声压级：峰值，20毫秒，带滤波粉红噪声信号，根据IEC 60268-2，频率范围下限以上一个倍频程，扬声器预设
重量：净重，不含可选设备
截止频率：在消声半空间条件下，扬声器预设 -10 dB

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
德国

电话 +49 7022 93323-0
传真 +49 7022 93324-0
www.fohhn.com
info@fohhn.com

